KINGLIFT
OFF ROAD SCISSOR LIFT



HIGHLIGHTS

High Performance

- Suitable for special uneven surfaces
- Foldable fence reduces the overall size of the machine
- Solid tires with strong grip performance
- Ground clearance of 200mm, excellent performance through
- 45% climbing ability, able to smoothly climb slopes
- Automatic display of fault codes for easy maintenance
- The pedal extension platform can be extended in both directions to the working point

FEATURES

Safety Configuration

Automatic braking system
Fault diagnosis system
Emergency descent system
Charging protection system
Emergency stop button
Tilt protection system
Oil pipe explosion-proof system
Sound alarm prompt system
Safety maintenance support rod
Platform self-locking door
One click quick leveling

Other Configuration

Proportional control
Buzzer
Strobe light
Bidirectional Extension Platform
Continuously variable transmission
Folding fence
horn
Transport forklift hole
Hour meter

www.kingliftcn.com

CE | EAC | TUV | ISO | CCC | IPAF

DETAILED PARAMETERS OF KINGLIFT
OFF ROAD SCISSOR LIFT

Model	QYCY-16RT
Size	
Working Height	17.80m
A-Platform Height-Elevated	15.8m
B-Platform Height-Stowed	2.09m
C-Platform Length	4.24m
D-Platform Width	1.83m
Platform Extension	1.3m
E-Overall Height (unfolded guardrail)	3.19m
Overall height (folded guardrail)	2.63m
F-Overall Length	1.88m
G-Overall Width	2.29m
H-Wheelbase	2.84m
I-Ground Clearance (Stowed)	0.2m
J-Ground Clearance (Raised)	0m
Performance	
Platform Capacity	680kg
Max. Number of Workers	4person
Driving Speed (Strowed)	6.1km/h
Driving Speed (Raised)	0.5km/h
Turning Radius (Outside)	5.5m
Turning Radius (Inside)	2.4m
Gradeability	0.45
Max. Working Angle	2°/3°
Tire(Drive Wheel)	33*12-20
Power	
Hydraulic oil tank	110L
Diesel fuel tank	150L
Power source (battery)	YangMAR/weichai
Weight	
Gross	8800KG





